

TBS30EA/TBS60EA

Electric Tractor 3.0 / 6.0t

TBS30EA / TBS60EA

Electric Tractor 3.0t / 6.0t

Disting	guishing mark				
1.1	Model designation			TBS30EA	TBS60EA
1.2	Drive unit			Electric	Electric
.3	Type of operation			Seated	Rider seated
1.4	Load capacity	Q	kg		6000
i. 4	Rated drawbar pull	F	N	3000 750	1200
1.6	Wheelbase	у	mm		1110
Veigh		y	111111	930	1110
2.1	Service weight (include battery)		kg	970	1150
2.2	Axle loading, unladen front/rear		kg	510/460	500/650
Гуре, (Chassis				
3.1	Tyre type			Solid rubber	Pneumatic
3.2	Tyre size, front			4.00-8	4.00-8
3.3	Tyre size, rear			4.00-8	4.00-8
3.4	Wheels, number front/rear (x=drive wheels)			1/2x	1/2x
3.5	Track rear	b ₁₁	mm	870	869
Dimen	sions				
1.1	Height of overhead guard (cabin)	h ₆	mm	1300	1320
1.2	Seat height	h ₇	mm	910	947
4.3	Tow coupling height	h _{10/a/b}	mm	305/350/395	318/390 (248/320, 388/460
4.4	Rear overhang	I ₅	mm	365	471
4.5	Loading platform, width	b ₉	mm	/	700
4.6	Overall length	I ₁	mm	1730	1966
4.7	Overall width	b ₁ /b ₂	mm	985	990/1010
4.8	Ground clearance, center of wheelbase	m ₂	mm	150	150
4.9	Outer turning radius	Wa	mm	1575	1800
4.10	Inner turning radius	b ₁₃	mm	-	677
Perfor	mance data				
5.1	Travel speed. laden/unladen		km/h	7/15	7/17
5.2	Maximum drawbar pull, laden/unladen S ₂ 5min.		N	3000	4500
5.3	Maximum gradeability, laden/unladen S ₂ 5min.		%	5/20	5/20
5.4	Service brake type			Hydraulic / Mechanical	Hydraulic / Mechanical
Drive					
6.1	Drive motor rating S2 60min		kW	4	6
6.2	Battery voltage / rated capacity (5h)		V/Ah	48/240	48/275
6.3	Battery weight		kg	433	506
Others					
7.1	Driver control			AC / zapi	AC / zapi
7.2	Sound level at operator's ear		dB(A)	70	70
7.3	Tow coupling			PIN	PIN

Note: The truck maximum operating hours per charge is dependent on the nature of tasks assigned. For more information on the truck functionality, features, and other customization options, please contact your nearest dealership for assistance.

UNPARALLED resilience to endure UNBEATABLE toughness

Robust and durable, the TBS-EA series is a **sit-down drive version** specifically tailored to exceed expectations that compose of **longer drive endurance** and **remarkable vigor qualities** to haul cargo goods that can last for at least a single work shift per charge.

Available in either **3.0T or 6.0T chassis**, the TBS-EA series allows the operator to shuttle through both indoor and outdoor environment easily without needing to fear the ground conditions as the truck is built with a **higher ground clearance** to overcome common gradient obstacles.

Capable of travelling up to a **maximum towing speed of 9.5km/hr**, the TBS-EA is an optimal choice to satisfy **TOUGH** requirements while accomplishing **SAFE** operation round the clock.



Quick Battery Change

Side battery² loading design allows the battery to be interchanged easily

High Performance AC drive system

- Smooth travel speed control up to 17km/hr¹ at unladen condition
- Competitive and powerful rated AC drive motor performance

Smooth Controls


- Standard Battery discharge indicator (*Indicates operating hours, battery level and error code)
- Electric power steering with short control handle offers effortless steering to relieve the operator from fatigue

✓ Improved Reliability & Maintenance

- Quick release tow pins facilitate unlocking & locking of the tow hook easily
- Heavy duty hood offers protection for the motors against possible impacts, and minimal water ingression resulted from light showers
- Robust & maintenance free AC traction motor allows smooth travel transition from point to point
- IP54 ZAPI AC controller offers better protection against water & dust ingression
- High-quality AMP connectors and durable electrical harnesses

Safe for operating

- · Safety seat switch ensures operator to remain seated before starting the truck
- Electromagnetic braking system keeps the truck steady on-ramp movement and prevents it from rolling backward
- . Mechanical hand brakes bring the truck to a full stopping motion with brakes constantly engaged
- Standard combination lights ensure sufficient forward illumination and alert nearby pedestrians to keep clear
- Standard walk beside buttons allows the operator to perform fine adjustment to align the rear tow eye position
- Optional partial enclosed cabin keeps the operator out of the light rain condition



²A standard feature for TBS30EA and optional for TBS60EA







